

MicroSet

Electro-Magnetic Flow Meter MS FL 0117 – HDPE Body

FEATURE

- Full Bore Type
- Simple & cost effective construction
- Provides wide flow ranges
- Outstanding accuracy
- Operates over wide ranges of temperature & pressure
- Easy maintenance as no moving parts
- Pulsed DC coil excitation
- Integral grounding
- Remote Electronics



PLASTIC / HDPE
ELECTROMAGNETIC FLOWMETER
WITH REMOTE FLOW INDICATOR
TOTALISER

SPECIFICATION

Media	: Liquids
Viscosity	: 200 cp max
Conductivity	: Minimum 10 μ S/cm
Line Size	: 25~ 150 mm NB
Excitation	: Pulsed DC coil
Type of Output	: 4~20 mA DC Isolated
Calibration Range	: As per requirement (Factory Calibrated)
Accuracy	: \pm 0.5% FS
Linearity	: \pm 0.5%
Repeatability	: \pm 1%
Process Temperature	: 60°C max
Process Pressure	: 5 kg/cm ²
Material of Construction of Sensor	: Hastelloy C / SS 316L
Body	: HDPE
Wetted Parts	: HDPE
Power Supply	: 230 VAC, 50Hz \pm 10%
Power Consumption	: <10 VA
Response Time	: <100 ms
Temperature Coefficient	: \pm 0.01% /°C
Transmitter Enclosure	: IP 65
Process Connections	: Threaded BSP
Operating Conditions	: Temp 0~55°C / Humidity 5~95% non-condensing

MicroSet Instrumentation & Controls

102, Chinmay, 1103/A/10, Lakaki Road, Model Colony, Shivaji Nagar, Pune, Maharashtra – 411 016, INDIA

TeleFax: +91-20-2566 0109

Email: microset@vsnl.net, microset@rediffmail.com Web: <http://www.microsetindia.com>